

INDUSTRIAL COMPONENT DATA

7409422 OBO BETTERMANN COVER AND FRAME TUB RKFR2 4 V20

Brand: OBO BETTERMANN | Manufacturer Part Number: RKFR2 4 V20



Manufacturer	OBO BETTERMANN
MPN / Reference	RKFR2 4 V20
Catalog number	7409422
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-F557D3967B
Generated	2026-08-01

Product Overview

COVER AND FRAME TUB RKFR2 4 V20

Height-adjustable cassette for tube body, RKFR, stainless steel. Height-adjustable cassette of nominal size R4 for tube body for installation of accessories in dry or wet-cleaned floors for indoor use. Height-adjustable cassette for tube body, 2-compartment. 2 APMT2 cover plates can be installed. For the installation of two UT3 universal supports for four single accessories with support ring/support clamp or six Modul 45 devices. The tube body is not contained in the scope of delivery.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN
--------------	---

Additional Product Information

Approvals VDE

Cable outlet version Lowerable tube body

CO2 Footprint (GWP) Cradle-to-Gate 12,3599 kg CO2e / 1 Piece

Decouplable no

Device support to accept mounting boxes yes

Dimension Ø215mm

Floor care Wet

Floor covering thickness 20 mm

Floor height, max. 155 mm

Floor height, min. 110 mm

Heavy-duty version no
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation diameter 215
Installation system type UT3
Length 214 mm
Material Stainless steel 1.4301
Nominal size for device installation units R4
Number of cable outlets 1
Number of installable devices 6
Number of mounting boxes 2
Protection rating (IP) when unused IP44
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 214 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKFR2 4 V20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.