

INDUSTRIAL COMPONENT DATA

7409430 OBO BETTERMANN COVER AND FRAME TUB RKFR2 9 V20

Brand: OBO BETTERMANN | Manufacturer Part Number: RKFR2 9 V20



Manufacturer	OBO BETTERMANN
MPN / Reference	RKFR2 9 V20
Catalog number	7409430
Category	Levelling cassette for duct mounting, raised and underfloor installation
Minimum order	1 Pcs
Document ID	EO-2193644F30
Generated	2026-08-01

Product Overview

COVER AND FRAME TUB RKFR2 9 V20

Height-adjustable cassette for tube body, RKFR, stainless steel. Height-adjustable cassette of nominal size R9 for tube body for installation of accessories in dry or wet-cleaned floors for indoor use. Height-adjustable cassette for tube body, 3-compartment. 3 APMT5 cover plates can be installed. For the installation of three UT4 universal supports for nine single accessories with support ring/support clamp or 12 Modul 45 devices. The tube body is not contained in the scope of delivery. Height-adjustable round cassette, 3-compartment, for tube bodies of nominal size 9 for the installation of accessories. Cassette for the use in trunking systems and in raised and cavity floors in dry- or wet-cleaned floors in indoor areas. Suitable only for smooth floor coverings. Three cover plates APMT5 can

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > UFS Underfloor piping systems - OBO BETTERMANN**

Additional Product Information

Approvals VDE
Cable outlet version Lowerable tube body
CO2 Footprint (GWP) Cradle-to-Gate 19,5393 kg CO2e / 1 Piece
Decouplable no
Device support to accept mounting boxes yes
Dimension Ø305mm
Floor care Wet
Floor covering thickness 20 mm

Floor height, max. 155 mm
Floor height, min. 110 mm
Heavy-duty version no
Height-adjustment range, max. 155 mm
Height-adjustment range, min. 110 mm
Installation depth 110 mm
Installation diameter 305
Installation system type UT4
Length 304 mm
Material Stainless steel 1.4301
Nominal size for device installation units R9
Number of cable outlets 1
Number of installable devices 12
Number of mounting boxes 3
Protection rating (IP) when unused IP44
Protection rating (IP) when used IP20
Protection rating IK code IK10
Suitable for cavity floor installation yes
Suitable for raised floor installation yes
Version for Round
Vertical load, large area to 5,000 N
Vertical load, small area to 3,000 N
Width 304 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / RKFR2 9 V20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.