

INDUSTRIAL COMPONENT DATA

AZK A 050 FT 6076149 OBO BETTERMANN CHANNEL FOR SMALL-TO-Z AZK A 050 FT

Brand: OBO BETTERMANN | Manufacturer Part Number: AZK A 050 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	AZK A 050 FT
Catalog number	6076149
Category	Cable tray/wide span cable tray
Minimum order	3 m.
Document ID	EO-88043829FF
Generated	2026-08-02

Product Overview

CHANNEL FOR SMALL-TO-Z AZK A 050 FT

Small channel A-Z, specific drilling, 50x50x3000, hot dip galvanized steel, DIN EN ISO 1461

AZ small duct 50 FT, without side windows. AZ channel with a side height of 50 mm.Magnetic shield insulation without cover 20 dB, with cover 50 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 3,963 kg CO2e / 1 Meter

Colour zinc

Connector version Without connectors

Dimension 50x50x3000

Height 50 mm

Length 3000 mm

Maintain electrical functions no

Material Steel

Mounting perforation in base yes

NATO hole pattern no

Plate thickness 1,5 mm

Rustproof steel, pickled no

Side perforation yes
Support spacing 1.0 m 3 kN/m
Support spacing 1.5 m 2,5 kN/m
Support spacing 2.0 m 1,7 kN/m
Support spacing 2.5 m 0,85 kN/m
Support spacing 3.0 m 0,5 kN/m
Surface Hot-dip galvanised
Usable cross-section 2500 mm²
Usable cross-section 25 cm²
Wide-span version no
Width 50 mm
ETIM for 6076149 Cable tray, ladder and wire basket systems (EC000047)
Feature Name
Feature Value
Height (EF000040)
50 mm
Width (EF000008)
50 mm
Material thickness (EF000386)
1.5 mm
Length (EF001438)
3000 mm
Useful cross section (EF005140)
2500 mm²
Side perforation (EF001122)
Yes
Bottom perforation (EF004545)
Yes
NATO-mounting holes (EF006059)
No
Model (EF000010)
Coupler not included
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Hot dip galvanized
Weight (EF000167)
1.66 kg/m
Possible support spacing (EF017261)
1 m
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)
3000
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
2500
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

1700

Safe working load according to IEC 61537 with support spacing 2.5 m (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / AZK A 050 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.