

INDUSTRIAL COMPONENT DATA

BS-F3-K-22 FT 1188207 OBO BETTERMANN BS-F3-K-22 FT 16-22mm Steel, St Hot-dipped Galvanized, DIN EN ISO 1461

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-F3-K-22 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	BS-F3-K-22 FT
Catalog number	1188207
Category	Fieldbus, decentr. periphery - communication module
Minimum order	50 Pcs
Document ID	EO-CEAA8419F0
Generated	2026-08-06

Product Overview

BS-F3-K-22 FT 16-22mm Steel, St Hot-dipped Galvanized, DIN EN ISO 1461

Clamp on profile 2056 BS-F3-K-22 FT, triple 16-22mm Steel, St, Hot dipped galvanized, DIN EN ISO 1461

Clamp clip 2056, F foot, single, plastic pressure trough, FT. Clamp clip with F-foot, plastic pressure trough made of polypropylene. For vertical and horizontal mounting of 3 single cables on flat bars. With 1-start screw thread on pressure trough, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for mounting indoors and outdoors. Multiple cables should be separated by double troughs. We recommend the use of a counter-trough.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN
--------------	--

Additional Product Information

Clamping range D, max. 22 mm

Clamping range D, min. 16 mm

CO2 Footprint (GWP) Cradle-to-Gate 0,2081 kg CO2e / 1 Piece

Dimension 16-22mm

Dimension A 22,5 mm

Dimension B 27 mm

Dimension C 34 mm

Dimension G (mm) M6

Dimension H 112 mm

Dimension L 59 mm

Dimension t 1,5 mm
For pipe diameter, max. 22 mm
For pipe diameter, min. 16 mm
Halogen-free yes
Height 112 mm
Length 22,5 mm
Length of external dimensions 34 mm
Material Steel
Material addition Steel
Max. Tightening torque 3 Nm
Mounting type Flat profile
Number of cables/pipes 3
Plate thickness 1,5 mm
Slot width 10 mm
Surface Hot-dip galvanised
Surface addition hot galvanised
Thread M6
Width 27 mm
With plastic trough yes
ETIM for 1188207 Cable and tube fixings (EC000454)
Feature Name
Feature Value
Chucking range (EF002391)
16 mm
For pipe size metric (M..) (EF004713)
22
Max. number of cables (EF001052)
3
Material clamp (EF006530)
Steel
Surface protection clamp (EF005142)
Hot dip galvanized
Surface protection shell (EF014680)
Hot dip galvanized
Material screw (EF006529)
Steel
Surface protection screw (EF005143)
Hot dip galvanized
Mounting method (EF000003)
Flat profile
Halogen free (EF000025)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-F3-K-22 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.