

INDUSTRIAL COMPONENT DATA

BS-H1-K-34 ALU 1186429 OBO BETTERMANN Clamp on profile 2056 BS-H1-K-34 ALU Steel, St Aluminum, Alu

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-H1-K-34 ALU



Manufacturer	OBO BETTERMANN
MPN / Reference	BS-H1-K-34 ALU
Catalog number	1186429
Category	One-piece strut clamp
Minimum order	100 Pcs
Document ID	EO-B5E6E9784C
Generated	2026-08-06

Product Overview

Clamp on profile 2056 BS-H1-K-34 ALU Steel, St Aluminum, Alu
Clamp on profile 2056 BS-H1-K-34 ALU, 28-34mm Aluminum, Alu,
Clamp clip 2056 H-foot 1-fold, plastic pressure sleeve, Al. Clamp clip with hammerhead foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For a slot width 16-17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN
--------------	--

Additional Product Information

Clamping range D, max. 34 mm
Clamping range D, min. 28 mm
CO2 Footprint (GWP) Cradle-to-Gate 0,3078 kg CO2e / 1 Piece
Dimension 28-34mm
Dimension A 22,5 mm
Dimension B 39 mm
Dimension C 34 mm
Dimension G (mm) M6
Dimension H 67 mm
Dimension L 47 mm

Dimension t 2 mm
For pipe diameter, max. 34 mm
For pipe diameter, min. 28 mm
for rail with slot width (with interval), max. 17 mm
for rail with slot width (with interval), min. 16 mm
Halogen-free yes
Height 67 mm
Length 22,5 mm
Length of external dimensions 34 mm
Material Aluminium
Material addition Aluminium
Material of trough Plastic
Material quality of trough Polypropylene
Max. Tightening torque 2 Nm
Mounting type Profile rail
Number of cables/pipes 1
Plate thickness 2 mm
Slot width 10 mm
Surface addition Untreated
Thread M6
Width 39 mm
With counter-trough no
With plastic trough yes
ETIM for 1186429 Cable and tube fixings (EC000454)
Feature Name
Feature Value
Chucking range (EF002391)
28 mm
For pipe size metric (M..) (EF004713)
34
Max. number of cables (EF001052)
1
Material clamp (EF006530)
Aluminium
Material shell (EF014679)
Plastic
Material quality shell (EF014685)
Polypropylene (PP)
Material screw (EF006529)
Aluminium
Material quality screw (EF014686)
Other
With counter shell (EF014681)
No
Mounting method (EF000003)
Profile rail
Halogen free (EF000025)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-H1-K-34 ALU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.