

INDUSTRIAL COMPONENT DATA

BS-H1-K-64 FT 1186262 OBO BETTERMANN Clamp on profile 2056 BS-H1-K-64 FT Steel, St Steel, St Hot-dip galvani..

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-H1-K-64 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	BS-H1-K-64 FT
Catalog number	1186262
Category	One-piece strut clamp
Minimum order	100 Pcs
Document ID	EO-73945AAFDA
Generated	2026-08-04

Product Overview

Clamp on profile 2056 BS-H1-K-64 FT Steel, St Steel, St Hot-dip galvanized, DIN EN ISO 1461

Clamp on single H-base profile, plastic half-rod, FT 2.5 mm M8 58-64mm

Clamp clip 2056 H-foot, 1-fold, plastic pressure sleeve, FT. Clamp clip with hammerhead foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For a slot width 16-17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Clamps BSS**

Additional Product Information

Clamping range D, max. 64 mm

Clamping range D, min. 58 mm

CO2 Footprint (GWP) Cradle-to-Gate 0,3103 kg CO2e / 1 Piece

Dimension 58-64mm

Dimension A 25 mm

Dimension B 70 mm

Dimension C 40 mm

Dimension G (mm) M8

Dimension H 102 mm

Dimension L 45 mm

Dimension t 2,5 mm
For pipe diameter, max. 64 mm
For pipe diameter, min. 58 mm
for rail with slot width (with interval), max. 17 mm
for rail with slot width (with interval), min. 16 mm
Halogen-free yes
Height 102 mm
Length 25 mm
Length of external dimensions 40 mm
Material Steel
Material addition Steel
Material of trough Plastic
Material quality of trough Polypropylene
Max. Tightening torque 5 Nm
Mounting type Profile rail
Number of cables/pipes 1
Plate thickness 2,5 mm
Slot width 10 mm
Surface Hot-dip galvanised
Surface addition hot galvanised
Thread M8
Width 70 mm
With counter-trough no
With plastic trough yes
ETIM for 1186262 Cable and tube fixings (EC000454)
Feature Name
Feature Value
Chucking range (EF002391)
58 mm
For pipe size metric (M..) (EF004713)
64
Max. number of cables (EF001052)
1
Material clamp (EF006530)
Steel
Surface protection clamp (EF005142)
Hot dip galvanized
Material shell (EF014679)
Plastic
Material quality shell (EF014685)
Polypropylene (PP)
Surface protection shell (EF014680)
Hot dip galvanized
Material screw (EF006529)
Steel
Surface protection screw (EF005143)
Hot dip galvanized

With counter shell (EF014681)

No

Mounting method (EF000003)

Profile rail

Halogen free (EF000025)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-H1-K-64 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.