

**INDUSTRIAL COMPONENT DATA**

# BS-H1-K-82 FT 1186282 OBO BETTERMANN Clamp on profile 2056 BS-H1-K-82 FT Stainless steel 1.4301, A2, 1.4301 ..

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-H1-K-82 FT



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | OBO BETTERMANN        |
| MPN / Reference | BS-H1-K-82 FT         |
| Catalog number  | 1186282               |
| Category        | One-piece strut clamp |
| Minimum order   | 25 Pcs                |
| Document ID     | EO-CB0646EFFC         |
| Generated       | 2026-08-04            |

## Product Overview

Clamp on profile 2056 BS-H1-K-82 FT Stainless steel 1.4301, A2, 1.4301 Steel, St Hot dipped galvanized, DIN EN ISO 1461

Clamp on single H-base profile, plastic half-rod, FT 2.5 mm M8 76-82 mm

Clamp clip 2056 H-foot, 1-fold, plastic pressure sleeve, FT. Clamp clip with hammerhead foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For a slot width 16-17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Clamps BSS**

## Additional Product Information

Clamping range D, max. 82 mm

Clamping range D, min. 76 mm

CO2 Footprint (GWP) Cradle-to-Gate 0,4838 kg CO2e / 1 Piece

Dimension 76-82mm

Dimension A 25 mm

Dimension B 88 mm

Dimension C 40 mm

Dimension G (mm) M8

Dimension H 122 mm

Dimension L 58 mm  
Dimension t 2,5 mm  
For pipe diameter, max. 82 mm  
For pipe diameter, min. 76 mm  
for rail with slot width (with interval), max. 17 mm  
for rail with slot width (with interval), min. 16 mm  
Halogen-free yes  
Height 122 mm  
Length 25 mm  
Length of external dimensions 40 mm  
Material Steel  
Material addition Steel  
Material of trough Plastic  
Material quality of trough Polypropylene  
Max. Tightening torque 5 Nm  
Mounting type Profile rail  
Number of cables/pipes 1  
Plate thickness 2,5 mm  
Slot width 10 mm  
Surface Hot-dip galvanised  
Surface addition hot galvanised  
Thread M8  
Width 88 mm  
With counter-trough no  
With plastic trough yes  
ETIM for 1186282 Cable and tube fixings (EC000454)  
Feature Name  
Feature Value  
Chucking range (EF002391)  
76 mm  
For pipe size metric (M..) (EF004713)  
82  
Max. number of cables (EF001052)  
1  
Material clamp (EF006530)  
Steel  
Surface protection clamp (EF005142)  
Hot dip galvanized  
Material shell (EF014679)  
Plastic  
Material quality shell (EF014685)  
Polypropylene (PP)  
Surface protection shell (EF014680)  
Hot dip galvanized  
Material screw (EF006529)  
Steel  
Surface protection screw (EF005143)

Hot dip galvanized  
With counter shell (EF014681)  
No  
Mounting method (EF000003)  
Profile rail  
Halogen free (EF000025)  
Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-H1-K-82 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.