

INDUSTRIAL COMPONENT DATA

BS-H1-M-34 A2 1186129 OBO BETTERMANN Clamp on profile 2056 BS-H1-M-34 A2 Stainless steel 1.4301, A2, 1.4301 ..

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-H1-M-34 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	BS-H1-M-34 A2
Catalog number	1186129
Category	Terminal block connector
Minimum order	25 Pcs
Document ID	EO-0AC91D50FE
Generated	2026-08-06

Product Overview

Clamp on profile 2056 BS-H1-M-34 A2 Stainless steel 1.4301, A2, 1.4301 Stainless steel 1.4301, A2, 1.4301 Polished, with post-treatment

Clamp on profile 2056 BS-H1-M-34 A2, 28-34mm Stainless steel 1.4301, A2, 1.4301, Polished, with subsequent treatment
 Clamp clip 2056 H-foot, 1-fold, metal pressure sleeve, A2. Clamp clip with hammerhead foot, metal pressure sleeve with rounded edges to protect the cable. For vertical and horizontal mounting of 1 single cable on a C-profile rail. For a slot width 16-17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. We recommend the use of a counter-sleeve.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN
--------------	--

Additional Product Information

Clamping range D, max. 34 mm
 Clamping range D, min. 28 mm
 CO2 Footprint (GWP) Cradle-to-Gate 0,3798 kg CO2e / 1 Piece
 Dimension 28-34mm
 Dimension A 22,5 mm
 Dimension B 39 mm
 Dimension C 34 mm
 Dimension G (mm) M6
 Dimension H 67 mm

Dimension L 46 mm
Dimension t 2 mm
For pipe diameter, max. 34 mm
For pipe diameter, min. 28 mm
for rail with slot width (with interval), max. 17 mm
for rail with slot width (with interval), min. 16 mm
Halogen-free yes
Height 67 mm
Length 22,5 mm
Length of external dimensions 34 mm
Maintain electrical functions yes
Material Stainless steel 1.4301
Material addition Rustproof steel
Material of trough Rustproof steel
Material quality of trough Stainless steel 304 (1.4301)
Max. Tightening torque 3 Nm
Mounting type Profile rail
Number of cables/pipes 1
Plate thickness 2 mm
Slot width 10 mm
Surface Bright, treated
Surface addition Untreated
Thread M6
Width 39 mm
With counter-trough no
With metal trough yes
With plastic trough no
ETIM for 1186129 Cable and tube fixings (EC000454)
Feature Name
Feature Value
Chucking range (EF002391)
28 mm
For pipe size metric (M..) (EF004713)
34
Max. number of cables (EF001052)
1
Material clamp (EF006530)
Stainless steel
Material quality clamp (EF014684)
Stainless steel 304 (1.4301)
Surface protection clamp (EF005142)
Untreated
Material shell (EF014679)
Stainless steel
Material quality shell (EF014685)
Stainless steel 304 (1.4301)
Surface protection shell (EF014680)

Untreated

Material screw (EF006529)

Stainless steel

Materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-H1-M-34 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.