

**INDUSTRIAL COMPONENT DATA**

# BS-H3-K-34 ALU 1186431 OBO BETTERMANN Clamp on profile 2056 BS-H3-K-34 ALU, triple Stainless steel 1.4301, A..

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-H3-K-34 ALU



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | OBO BETTERMANN                   |
| MPN / Reference | BS-H3-K-34 ALU                   |
| Catalog number  | 1186431                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 50 Pcs                           |
| Document ID     | EO-686F878A5E                    |
| Generated       | 2026-08-06                       |

## Product Overview

Clamp on profile 2056 BS-H3-K-34 ALU, triple Stainless steel 1.4301, A2, 1.4301 Aluminum, Alu  
Clamp on profile 2056 BS-H3-K-34 ALU, triple 28-34mm Aluminum, Alu,  
Clamp clip 2056 H-foot, 3-fold, plastic pressure sleeve, Al. Clamp clip with hammerhead foot, plastic pressure sleeve made of polypropylene. For vertical and horizontal mounting of 3 single cables on a C-profile rail. For a slot width 16-17 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. Multiple cables should be separated by double sleeves. We recommend the use of a counter-sleeve.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN**

## Additional Product Information

Clamping range D, max. 34 mm  
Clamping range D, min. 28 mm  
CO2 Footprint (GWP) Cradle-to-Gate 0,5592 kg CO2e / 1 Piece  
Dimension 28-34mm  
Dimension A 22,5 mm  
Dimension B 39 mm  
Dimension C 34 mm  
Dimension G (mm) M6  
Dimension H 141 mm

Dimension L 59 mm  
Dimension t 2 mm  
For pipe diameter, max. 34 mm  
For pipe diameter, min. 28 mm  
for rail with slot width (with interval), max. 17 mm  
for rail with slot width (with interval), min. 16 mm  
Halogen-free yes  
Height 141 mm  
Length 22,5 mm  
Length of external dimensions 34 mm  
Material Aluminium  
Material addition Aluminium  
Material of trough Plastic  
Material quality of trough Polypropylene  
Max. Tightening torque 2 Nm  
Mounting type Profile rail  
Number of cables/pipes 3  
Plate thickness 2 mm  
Slot width 10 mm  
Surface addition Untreated  
Thread M6  
Width 39 mm  
With counter-trough no  
With plastic trough yes  
ETIM for 1186431 Cable and tube fixings (EC000454)  
Feature Name  
Feature Value  
Chuckling range (EF002391)  
28 mm  
For pipe size metric (M..) (EF004713)  
34  
Max. number of cables (EF001052)  
3  
Material clamp (EF006530)  
Aluminium  
Material shell (EF014679)  
Plastic  
Material quality shell (EF014685)  
Polypropylene (PP)  
Material screw (EF006529)  
Aluminium  
Material quality screw (EF014686)  
Other  
With counter shell (EF014681)  
No  
Mounting method (EF000003)  
Profile rail

Halogen free (EF000025)

Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-H3-K-34 ALU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.