

INDUSTRIAL COMPONENT DATA

BS-U2-M-16 FT 1186510 OBO BETTERMANN Clamp on profile 2056 BS-U2-M-16 FT, double Brass, CuZn Steel, St Hot d..

Brand: OBO BETTERMANN | Manufacturer Part Number: BS-U2-M-16 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	BS-U2-M-16 FT
Catalog number	1186510
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	50 Pcs
Document ID	EO-6394FC150C
Generated	2026-08-05

Product Overview

Clamp on profile 2056 BS-U2-M-16 FT, double Brass, CuZn Steel, St Hot dip galvanized, DIN EN ISO 1461
Clamp on profile 2056 BS-U2-M-16 FT, double 12-16mm Steel, St, Hot dipped galvanized, DIN EN ISO 1461
Clamp clip 2056 U-foot, 2-fold, metal pressure sleeve, FT. Clamp clip with U-foot, metal pressure sleeve with rounded edges to protect the cable. For vertical and horizontal mounting of 2 single cables on a C-profile rail. For slot width 18-22 mm. With 1-start screw thread on pressure sleeve, universal hexagonal screw head WAF10, with slot and cross recess. Suitable for assembly indoors and outdoors. Multiple cables should be separated by double sleeves. We recommend the use of a counter-sleeve.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN**

Additional Product Information

Clamping range D, max. 16 mm
Clamping range D, min. 12 mm
CO2 Footprint (GWP) Cradle-to-Gate 0,1435 kg CO2e / 1 Piece
Dimension 12-16mm
Dimension A 22,5 mm
Dimension B 20 mm
Dimension C 28 mm
Dimension G (mm) M6
Dimension H 65 mm

Dimension L 46 mm
Dimension t 1,5 mm
For pipe diameter, max. 16 mm
For pipe diameter, min. 12 mm
for rail with slot width (with interval), max. 22 mm
for rail with slot width (with interval), min. 18 mm
Halogen-free yes
Height 65 mm
Length 22,5 mm
Length of external dimensions 28 mm
Maintain electrical functions yes
Material Steel
Material addition Steel
Material of trough Steel
Max. Tightening torque 3 Nm
Mounting type Profile rail
Number of cables/pipes 2
Plate thickness 1,5 mm
Slot width 10 mm
Surface Hot-dip galvanised
Surface addition hot galvanised
Thread M6
Width 20 mm
With counter-trough no
With metal trough yes
With plastic trough no
ETIM for 1186510 Cable and tube fixings (EC000454)
Feature Name
Feature Value
Chucking range (EF002391)
12 mm
For pipe size metric (M..) (EF004713)
16
Max. number of cables (EF001052)
2
Material clamp (EF006530)
Steel
Surface protection clamp (EF005142)
Hot dip galvanized
Material shell (EF014679)
Steel
Surface protection shell (EF014680)
Hot dip galvanized
Material screw (EF006529)
Steel
Surface protection screw (EF005143)
Hot dip galvanized

With counter shell (EF014681)

No

Mounting method (EF000003)

Profile rail

Halogen free (EF000025)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / BS-U2-M-16 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.