INDUSTRIAL COMPONENT DATA

V-TEC VM20+ OR 7205660 OBO BETTERMANN Cable gland with locknut, M20, Pastel orange, 2003, Polyamide, fibregl..

Brand: OBO BETTERMANN | Manufacturer Part Number: V-TEC VM20+ OR

Manufacturer	OBO BETTERMANN
MPN / Reference	V-TEC VM20+ OR
Catalog number	7205660
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-2E46B7EF77
Generated	2026-08-01

Product Overview

Cable gland with locknut, M20, Pastel orange, 2003, Polyamide, fibreglass reinforced, PA/GF
Cable gland with locknut as a set. Robust cap nut cable gland with metric connecting thread to IEC 423, including pre-mounted locknut.For high tightness requirements. Strain relief, torsion protection and tightness over the whole clamping area. Sealing ring made of polychloroprene/acrylonitrile butadiene rubber. Moulded shaped sealing lip on intermediate support, no connection thread sealing ring required.VDE-tested according to DIN EN 50262, protection rating IP68 at 5 bar for 1 hr.For maintenance of electrical function according to DIN 4102 Part 12 in connection with the closed junction boxes of the FireBox T series.Colour: Pastel orange.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > BSS fire protection systems - OBO BETTERMANN

Additional Product Information

Bend protection no
CO2 Footprint (GWP) Cradle-to-Gate 0,0553 kg CO2e / 1 Piece
Colour Pastel orange; RAL 2003
Dimension M20
Dimension E 27 mm
Dimension E1 (mm) 27 mm
Dimension E2 27 mm
Dimension G M20 x 1,5 mm
Dimension L max. 30,5 mm

Dimension L min. 23,5 mm
Dimension L1 9 mm
Dimension L2 5 mm
Dimension L3 6 mm
Fibre-glass reinforced no
Flame-resistant acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Flat cable gland no
For Ex zone Without
For Ex zone dust Without
For Ex zone gas Without
Halogen-free yes
Impact-resistant no
Material Polyamide
Permitted temperature range, max. 65 °C
Permitted temperature range, min. -20 °C
Protection rating IP68
Sealing area D, max. 13 mm
Sealing area D, min. 6 mm
Sealing insert, multiple no
Splittable gland no
Strain relief option yes
Thread M20 x 1,5
Thread increase 1,5 mm
Thread length 9 mm
Thread type Metric
Unstable torque 3,8 Nm
WAF 24
WAF 1 24 mm
WAF 2 24 mm
With locknut yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / V-TEC VM20+ OR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.