

INDUSTRIAL COMPONENT DATA

2050 5-25 LGR 2254026 OBO BETTERMANN Series clip , 5-25mm, Light grey, 7035, Polystyrene, PS

Brand: OBO BETTERMANN | Manufacturer Part Number: 2050 5-25 LGR



Manufacturer	OBO BETTERMANN
MPN / Reference	2050 5-25 LGR
Catalog number	2254026
Category	Pipe saddle clamp
Minimum order	100 Pcs
Document ID	EO-F34C641ACD
Generated	2026-08-01

Product Overview

Series clip , 5-25mm, Light grey, 7035, Polystyrene, PS

Series clip, light grey. Also suitable for rails of 11 ÷ 12 mm slot width; polystyrene clip element, impact resistant, halogen-free, light grey RAL 7035; metal parts: electrogalvanised steel.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Clamps 2054

Additional Product Information

Bolt M4 x 30
 Clamping range D, max. 25 mm
 Clamping range D, min. 5 mm
 CO2 Footprint (GWP) Cradle-to-Gate 0,0219 kg CO2e / 1 Piece
 Colour Light grey; RAL 7035
 Dimension 5-25mm
 Dimension B 14 mm
 Dimension B1 7,5 mm
 Dimension H 24 mm
 Dimension H1 12,5 mm
 Distance to the wall no
 Fastening type Rail fastening
 for rail with slot width (with interval), max. 12 mm

for rail with slot width (with interval), min. 11 mm

Halogen-free yes

Impact-resistant no

Material Polystyrene

Nominal diameter 25 mm

Number of cables/pipes 1

Plastic-covered no

Suitable in fire protection area no

UV-resistant no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2050 5-25 LGR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.