

INDUSTRIAL COMPONENT DATA

2955 F M32 RW 2149369 OBO BETTERMANN Quick clip flame-resistant, M32, Pure white, 9010, Polypropylene, PP

Brand: OBO BETTERMANN | Manufacturer Part Number: 2955 F M32 RW



Manufacturer	OBO BETTERMANN
MPN / Reference	2955 F M32 RW
Catalog number	2149369
Category	Tube clamp
Minimum order	50 Pcs
Document ID	EO-4880602C1E
Generated	2026-08-04

Product Overview

Quick clip flame-resistant, M32, Pure white, 9010, Polypropylene, PP

Quick clip, flame-resistant, pure white. Flame-resistant, flush-mounted clip to accept metric steel armoured pipes and heavy-duty insulating pipes, as well as Quick-Pipe® electrical installation pipes. Universal fastening options on walls and ceilings, both in indoor and protected outdoor areas. With slot for side alignment during mounting with wood screw or knock-in anchor. Toolless pipe mounting. Can also be arranged with OBO Multi-Quick or proQuick clip. M16 - M32 size can be screwed onto M6 thread. Recommended fastening spacing 50-60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Clamps 2955**

Additional Product Information

Clamping range D, max. 32 mm
Clamping range D, min. 32 mm
Closed no
CO2 Footprint (GWP) Cradle-to-Gate 0,0287 kg CO2e / 1 Piece
Colour Pure white; RAL 9010
Dimension M32
Dimension A 46,3 mm
Dimension B 16 mm
Dimension C 22,4 mm

Dimension D 31,4 mm

Dimension E 12 mm

Dimension F 4,2 mm

Dimension H 42 mm

Dimension h 11 mm

Expandable yes

Fastening type Screw hole

Flame-resistant Acc. to VDE 0471/DIN 695 Part 2-1, test temperature 750°C

Halogen-free yes

Material Polypropylene

Nominal size M32

Number of cables/pipes 1

Pull-out value 100 N

UV-resistant no

With inlay no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2955 F M32 RW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.