

INDUSTRIAL COMPONENT DATA

2955 M25 2149016 OBO BETTERMANN Quick clip , M25, Light grey, 7035, Polypropylene, PP

Brand: OBO BETTERMANN | Manufacturer Part Number: 2955 M25



Manufacturer	OBO BETTERMANN
MPN / Reference	2955 M25
Catalog number	2149016
Category	Tube clamp
Minimum order	100 Pcs
Document ID	EO-EA01CB2ED3
Generated	2026-08-02

Product Overview

Quick clip , M25, Light grey, 7035, Polypropylene, PP

Quick Clamp 2955 M25, M25 Polypropylene, PP,

Quick clip, light grey. Flush-mounted clip to accept metric steel armoured pipes and heavy-duty insulating pipes, as well as Quick-Pipe® electrical installation pipes. Universal fastening options on walls and ceilings, both in indoor and protected outdoor areas. With slot for side alignment during mounting with wood screw or knock-in anchor. Toolless pipe mounting. Can also be arranged with OBO Multi-Quick or proQuick clip. M16 - M32 size can be screwed onto M6 thread.

Recommended fastening spacing 50-60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Clamps 2955

Additional Product Information

Breaking load 0,1 kN

Clamping range D, max. 25 mm

Clamping range D, min. 25 mm

Closed no

CO2 Footprint (GWP) Cradle-to-Gate 0,0189 kg CO2e / 1 Piece

Colour Light grey; RAL 7035

Dimension M25

Dimension A 36,3 mm

Dimension B 16 mm

Dimension C 17,5 mm
Dimension D 24,3 mm
Dimension E 12 mm
Dimension F 4,2 mm
Dimension h 10 mm
Dimension H 34 mm
Expandable yes
Fastening type Screw hole
Halogen-free yes
Material Polypropylene
Nominal size M25
Number of cables/pipes 1
Pull-out value 100 N
UV-resistant no
With inlay no
ETIM for 2149016 Cable and tube fixings (EC000368)
Feature Name
Feature Value
Closed (EF001228)
No
Material (EF002169)
Plastic
Material quality (EF001257)
Other
Connectable (EF006169)
Yes
Max. number of tubes (EF001225)
1
Type of fastening (EF002442)
Screw hole
With inlay (EF005913)
No
Colour (EF000007)
Grey
Halogen free (EF000025)
Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2955 M25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.