

**INDUSTRIAL COMPONENT DATA**

# 2955 M50 2149034 OBO BETTERMANN Quick clip , M50, Light grey, 7035, Polypropylene, PP

Brand: OBO BETTERMANN | Manufacturer Part Number: 2955 M50



|                 |                |
|-----------------|----------------|
| Manufacturer    | OBO BETTERMANN |
| MPN / Reference | 2955 M50       |
| Catalog number  | 2149034        |
| Category        | Tube clamp     |
| Minimum order   | 25 Pcs         |
| Document ID     | EO-69AC08E2C7  |
| Generated       | 2026-07-31     |

## Product Overview

Quick clip , M50, Light grey, 7035, Polypropylene, PP

Quick clip, light grey. Flush-mounted clip to accept metric steel armoured pipes and heavy-duty insulating pipes, as well as Quick-Pipe® electrical installation pipes. Universal fastening options on walls and ceilings, both in indoor and protected outdoor areas. With slot for side alignment during mounting with wood screw or knock-in anchor. Toolless pipe mounting. Can also be arranged with OBO Multi-Quick or proQuick clip. M16 - M32 size can be screwed onto M6 thread. Recommended fastening spacing 50-60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **OBO BETTERMANN > VBS Connection and fastening systems - OBO BETTERMANN > Clamps 2955**

## Additional Product Information

Breaking load 0,17 kN  
 Clamping range D, max. 50 mm  
 Clamping range D, min. 50 mm  
 Closed no  
 CO2 Footprint (GWP) Cradle-to-Gate 0,0608 kg CO2e / 1 Piece  
 Colour Light grey; RAL 7035  
 Dimension M50  
 Dimension A 70,3 mm  
 Dimension B 18 mm  
 Dimension C 32 mm

Dimension D 49 mm  
Dimension E 12 mm  
Dimension F 6 mm  
Dimension h 14 mm  
Dimension H 63 mm  
Expandable yes  
Fastening type Screw hole  
Halogen-free yes  
Material Polypropylene  
Nominal size M50  
Number of cables/pipes 1  
Pull-out value 135 N  
UV-resistant no  
With inlay no

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / 2955 M50 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.