

INDUSTRIAL COMPONENT DATA

MTG-X3F L AL1 6105216 OBO BETTERMANN Multimedia support, XLR, 3-pin socket w. soldered connection, 45x45mm, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: MTG-X3F L AL1



Manufacturer	OBO BETTERMANN
MPN / Reference	MTG-X3F L AL1
Catalog number	6105216
Category	Insert/cover for communication technology
Minimum order	1 Pcs
Document ID	EO-57BE3473AF
Generated	2026-08-01

Product Overview

Multimedia support, XLR, 3-pin socket w. soldered connection, 45x45mm, Aluminium painted, Polycarbonate, PC Multimedia socket, XLR, 3-pin MTG-X3F L AL1, Socket with welded connection 45x45mm Polycarbonate, PC, XLR connection, 1 module, straight outlet, 3-pin socket, as soldered connection, aluminium-painted. Multimedia support with one XLR connection socket, straight cable outlet, without labelling panel, 3-pin XLR socket with soldered connection. Support plate with locking fastening, suitable for horizontal and vertical installation in the system environment. For installation in Rapid 45 device installation ducts, Rapid 80 device installation ducts, service poles and underfloor systems.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > EGS device systems - OBO BETTERMANN > Systems mechanisms
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 0,0573 kg CO2e / 1 Piece
Colour Aluminium painted
Combination Basic element with central cover plate
Depth 9 mm
Dimension 45x45mm
Fastening type Lock
Halogen-free yes
Height 45 mm

Hinged cover no
Labelling panel With labelling panel
Lamp-wire connector no
Material Polycarbonate
Protection rating IP20
Strain relief option no
Support ring no
Surface version Matt
Transparent no
Use XLR
Width 45 mm
With dust protection no
With printed label no
ETIM for 6105216 Domestic wiring accessories and controls (EC000018)
Feature Name
Feature Value
Assembly arrangement (EF000005)
Basic unit with central cover plate
Utilization (EF000133)
XLR
Support ring (EF005709)
No
With dust cover (EF003893)
No
With hinged lid (EF000117)
No
Imprintable label (EF001519)
With indication plate
With imprint (EF004048)
No
Material (EF002169)
Plastic
Material quality (EF001257)
Other
Halogen free (EF000025)
Yes
Surface finishing (EF006569)
Matt
Colour (EF000007)
Aluminium
Transparent (EF006243)
No
Type of fastening (EF002442)
Engage (snap)
With strain relief (EF000878)
No
Luster terminal (EF003868)

No

Suitable for degree of protection (IP) (EF006755)

IP20

Device width (EF008808)

45 mm

Device height (EF008809)

45 mm

Device depth (EF008810)

9 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / MTG-X3F L AL1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.