

INDUSTRIAL COMPONENT DATA

LKVH 50037 6178582 OBO BETTERMANN Slotted cable trunking system halogen-free, 50x37,5x2000, Light grey, 7035..

Brand: OBO BETTERMANN | Manufacturer Part Number: LKVH 50037



Manufacturer	OBO BETTERMANN
MPN / Reference	LKVH 50037
Catalog number	6178582
Category	Slotted cable trunking system
Minimum order	48 Pcs
Document ID	EO-DD45A7A3CE
Generated	2026-08-01

Product Overview

Slotted cable trunking system halogen-free, 50x37,5x2000, Light grey, 7035, Polycarbonate/Acrylonitrile-butadiene-styrene, PC/ABS

LKVH 50037 halogen-free Frame Channel 50x37.5x2000 Light grey, RAL 7035

Polycarbonate/Acrylonitrile-butadiene-styrene, PC/ABS

Wiring trunking, type LKVH 50037. Halogen-free wiring duct according to DIN EN 50085-2-3, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a DIN duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tested to DIN EN 50085-2-3. Special lengths on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Halogen-Free Channel

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 2,5459 kg CO2e / 1 Meter

Colour Light grey; RAL 7035

Creepage current-resistant yes

Dimension 50x37,5x2000

Fastening type Base perforation

Flexible no

Halogen-free yes

Height 50 mm

Length 2000 mm
Material Polycarbonate/Acrylnitrile-butadiene-styrene
Permitted temperature range, max. 90 °C
Permitted temperature range, min. -25 °C
Self-extinguishing yes
Side wall version Slotted
Slot spacing 12,5 mm
Slot width 5 mm
Usable cross-section 14,24 cm²
Width 37,5 mm
With cover yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LKVH 50037 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.