

## INDUSTRIAL COMPONENT DATA

# LKVH N 75075 6178559 OBO BETTERMANN Slotted cable trunking system halogen-free, 75x75x2000, Light grey, 7035..

Brand: OBO BETTERMANN | Manufacturer Part Number: LKVH N 75075



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | OBO BETTERMANN                |
| MPN / Reference | LKVH N 75075                  |
| Catalog number  | 6178559                       |
| Category        | Slotted cable trunking system |
| Minimum order   | 16 m.                         |
| Document ID     | EO-266478A3E8                 |
| Generated       | 2026-08-03                    |

## Product Overview

Slotted cable trunking system halogen-free, 75x75x2000, Light grey, 7035, Polycarbonate/Acrylnitrile-butadiene-styrene, PC/ABS

Wiring trunking, type LKVH N 75075. Halogen-free wiring duct according to DIN EN 50085-2-3, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. Designed as a DIN duct. Retainers are broken out without tools. The flush-floor routing of cables is possible through predetermined break points. Tapering in the side slots prevents the cables from falling out. Tested to DIN EN 50085-2-3. Special lengths on request.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > LFS cable routing systems - OBO BETTERMANN > Halogen-Free Channel |
|--------------|------------------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 4,6423 kg CO2e / 1 Meter

Colour Light grey; RAL 7035

Creepage current-resistant yes

Dimension 75x75x2000

Fastening type Base perforation

Flexible no

Halogen-free yes

Height 75 mm

Length 2000 mm

Material Polycarbonate/Acrylnitrile-butadiene-styrene

Permitted temperature range, max. 90 °C  
Permitted temperature range, min. -25 °C  
Self-extinguishing yes  
Side wall version Slotted  
Slot spacing 12,5 mm  
Slot width 5 mm  
Usable cross-section 47,95 cm<sup>2</sup>  
Width 75 mm  
With cover yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LKVH N 75075 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.