

INDUSTRIAL COMPONENT DATA

ASX-E 7202312 OBO BETTERMANN Ablation coating in a bucket, 5kg, Intumescent material

Brand: OBO BETTERMANN | Manufacturer Part Number: ASX-E



Manufacturer	OBO BETTERMANN
MPN / Reference	ASX-E
Catalog number	7202312
Category	Fire protection compound/binding/foam/sealant
Minimum order	1 Pcs
Document ID	EO-D5F8B7865B
Generated	2026-07-29

Product Overview

Ablation coating in a bucket, 5kg, Intumescent material

Ablation coating PYROCOAT® in a bucket. Combined, endothermic and weatherproof coating for internal and external areas. Universal protection coating for cable and cable support structures. Use as direct filler, and as paint when stirred. Sufficient for an area of 4 m². Material class DIN 4102 - B2, normally flammable. In dry, frost-free rooms, the coating can be stored at temperatures from +5 °C to +25 °C for up to 18 months in closed, upright original containers.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > BSS fire protection systems - OBO BETTERMANN > Isolation

Additional Product Information

Colour White
 Contents 5 kg
 Delivery form Bucket
 Dimension 5kg
 Material Intumescent material

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / ASX-E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.