


**INDUSTRIAL COMPONENT DATA**

# G-GRM 125 75 G 6005541 OBO BETTERMANN G mesh cable tray Magic , 125x75x3000, Electrogalvanised, DIN 50961, S..

Brand: OBO BETTERMANN | Manufacturer Part Number: G-GRM 125 75 G



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | G-GRM 125 75 G  |
| Catalog number  | 6005541         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-700E1638CE   |
| Generated       | 2026-08-02      |

## Product Overview

G mesh cable tray Magic , 125x75x3000, Electrogalvanised, DIN 50961, Steel, St  
G-GRM G-GRM 125 75 G grid tray, 125x75x3000 Steel, St, electro-galvanized, EN ISO 19598 / EN ISO 4042  
G-mesh gutter Magic® 125 g

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Grid

## Additional Product Information

Magnetic shield insulation 15 dB.  
ETIM for 6005541 Cable tray, ladder and wire basket systems (EC000853)  
Feature Name  
Feature Value  
Profile shape (EF005179)  
G-shape  
Width (EF000008)  
75 mm  
Height (EF000040)  
125 mm  
Length (EF001438)  
3000 mm  
Diameter longitudinal wire (EF017247)

3.9 mm  
Diameter transverse wire (EF017380)  
3.9 mm  
Useful cross section (EF005140)  
6100 mm<sup>2</sup>  
Integrated partition (EF004799)  
None  
Model (EF000010)  
Integrated coupler  
Type of connector (EF000141)  
Click in  
Suitable for circuit integrity (EF007806)  
No  
Material (EF002169)  
Steel  
Surface protection (EF000139)  
Galvanic/electrolytic zinc plated  
Weight (EF000167)  
1.08 kg/m  
Load test type according to IEC 61537 (EF015362)  
Type II  
Possible support spacing (EF017261)  
1 m  
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)  
600  
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)  
350  
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)  
300  
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)  
250

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / G-GRM 125 75 G with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.