


**INDUSTRIAL COMPONENT DATA**

# G-GRM 50 50 FT 6005520 OBO BETTERMANN G mesh cable tray Magic , 50x50x3000, Hot-dip galvanised, DIN EN ISO 1..

Brand: OBO BETTERMANN | Manufacturer Part Number: G-GRM 50 50 FT



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | G-GRM 50 50 FT  |
| Catalog number  | 6005520         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-ECE580B918   |
| Generated       | 2026-07-31      |

## Product Overview

G mesh cable tray Magic , 50x50x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

G mesh cable tray Magic® 50 FT. G-shaped mesh cable tray made of spot-welded steel wire with different side heights and widths. Direct wall or ceiling mounting possible. Load capacity details regarding the different mounting methods are available upon request. Magnetic shield insulation 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid |
|--------------|--------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 1,4885 kg CO2e / 1 Meter

Colour zinc

Connector version Integrated connector

Dimension 50x50x3000

Dimension A 38 mm

Dimension B 55 mm

Dimension C 33 mm

Dimension H 55 mm

Height 50 mm

Height 1,97 in

Integrated partition Without

Length 3000 mm

Load test type according to IEC 61537 Type II  
Maintain electrical functions no  
Material Steel  
Profile shape G-shaped  
Rustproof steel, pickled no  
Screwless connector yes  
Surface Hot-dip galvanised  
Type of connector, cable support system Click fastening  
Usable cross-section 1700 mm<sup>2</sup>  
Usable cross-section 17 cm<sup>2</sup>  
Wide-span version no  
Width 50 mm  
Width 1,97 in  
Wire diameter 3,9 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / G-GRM 50 50 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.