


**INDUSTRIAL COMPONENT DATA**

# GRM 105 200 FT 6002435 OBO BETTERMANN Mesh cable tray

## GRM , 105x200x3000, Hot-dip galvanised, DIN EN ISO 146..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 105 200 FT



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | GRM 105 200 FT  |
| Catalog number  | 6002435         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-395408C694   |
| Generated       | 2026-08-01      |

### Product Overview

Mesh cable tray GRM , 105x200x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St  
GRM GRM 105 200 FT Grid Tray, 105x200x3000 Steel, St, Hot-dip Galvanized, DIN EN ISO 1461  
Mesh cable tray GR-Magic® 105 FT. Mesh cable tray with shaped connector of side height 105 mm.Magnetic shield insulation without cover 15 dB, with cover 25 dB.

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Grid

### Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 4,1707 kg CO2e / 1 Meter  
Colour zinc  
Connector version Integrated connector  
Dimension 105x200x3000  
Dimension B 200 mm  
Dimension H 108 mm  
Height 105 mm  
Height 4,13 in  
Integrated partition Without  
Length 3000 mm  
Load test type according to IEC 61537 Type II  
Maintain electrical functions no

Material Steel  
Profile shape U-shaped  
Rustproof steel, pickled no  
Screwless connector yes  
Support spacing 1.0 m 1 kN/m  
Support spacing 1.5 m 0,7 kN/m  
Support spacing 2.0 m 0,4 kN/m  
Support spacing 2.5 m 0,25 kN/m  
Support spacing 3.0 m 0,25 kN/m  
Surface Hot-dip galvanised  
Type of connector, cable support system Click fastening  
Usable cross-section 175 cm<sup>2</sup>  
Usable cross-section 17500 mm<sup>2</sup>  
Wide-span version no  
Width 200 mm  
Width 7,87 in  
Wire diameter 4,8 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 105 200 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.