

INDUSTRIAL COMPONENT DATA

GRM 105 300 G 6002408 OBO BETTERMANN Mesh cable tray

GRM , 105x300x3000, Electrogalvanised, DIN 50961, Steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 105 300 G



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 105 300 G
Catalog number	6002408
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-2B96EAB679
Generated	2026-08-02

Product Overview

Mesh cable tray GRM , 105x300x3000, Electrogalvanised, DIN 50961, Steel, St
 GRM GRM 105 300 G grid tray, 105x300x3000 Steel, St, electro-galvanized, EN ISO 19598 / EN ISO 4042
 Mesh cable tray GR-Magic® 105 G. Mesh cable tray with shaped connector of side height 105 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 4,3564 kg CO2e / 1 Meter
 Colour zinc
 Connector version Integrated connector
 Dimension 105x300x3000
 Dimension B 300 mm
 Dimension H 108 mm
 Height 4,13 in
 Height 105 mm
 Integrated partition Without
 Length 3000 mm
 Load test type according to IEC 61537 Type II
 Maintain electrical functions no

Material Steel
Profile shape U-shaped
Rustproof steel, pickled no
Screwless connector yes
Support spacing 1.0 m 1,6 kN/m
Support spacing 1.5 m 0,8 kN/m
Support spacing 2.0 m 0,5 kN/m
Support spacing 2.5 m 0,33 kN/m
Support spacing 3.0 m 0,3 kN/m
Surface Electrogalvanized
Type of connector, cable support system Click fastening
Usable cross-section 268 cm²
Usable cross-section 26800 mm²
Wide-span version no
Width 11,81 in
Width 300 mm
Wire diameter 4,8 mm
ETIM for 6002408 Cable tray, ladder and wire basket systems (EC000853)
Feature Name
Feature Value
Profile shape (EF005179)
U-shape
Width (EF000008)
300 mm
Height (EF000040)
105 mm
Length (EF001438)
3000 mm
Diameter longitudinal wire (EF017247)
4.8 mm
Diameter transverse wire (EF017380)
4.8 mm
Useful cross section (EF005140)
26800 mm²
Integrated partition (EF004799)
None
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Galvanic/electrolytic zinc plated
Weight (EF000167)

2.35 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1 m

Safe worki...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 105 300 G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.