


INDUSTRIAL COMPONENT DATA

GRM 35 100 A2 6000055 OBO BETTERMANN Mesh cable tray

GRM , 35x100x3000, Stainless steel, grade 304, VA, 1.43..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 35 100 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 35 100 A2
Catalog number	6000055
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-A2AA1C8793
Generated	2026-08-01

Product Overview

Mesh cable tray GRM , 35x100x3000, Stainless steel, grade 304, VA, 1.4301

GRM GRM 35 100 A2 Grid Tray, 35x100x3000 Stainless Steel 1.4301, A2, 1.4301, Polished, with Post Treatment

Mesh cable tray GR-Magic® 35 A2. Mesh cable tray with shaped connector of side height 35 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid
--------------	--

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 2,5382 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 35x100x3000

Dimension B 100 mm

Height 35 mm

Height 1 in

Integrated partition Without

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Stainless steel 1.4301

Profile shape U-shaped
Rustproof steel, pickled yes
Screwless connector yes
Support spacing 1.0 m 0,25 kN/m
Support spacing 1.5 m 0,11 kN/m
Support spacing 2.0 m 0,1 kN/m
Surface Bright, treated
Type of connector, cable support system Click fastening
Usable cross-section 3500 mm²
Usable cross-section 23 cm²
Wide-span version no
Width 100 mm
Width 4 in
Wire diameter 3,9 mm
ETIM for 6000055 Cable tray, ladder and wire basket systems (EC000853)
Feature Name
Feature Value
Profile shape (EF005179)
U-shape
Width (EF000008)
100 mm
Height (EF000040)
35 mm
Length (EF001438)
3000 mm
Diameter longitudinal wire (EF017247)
3.9 mm
Diameter transverse wire (EF017380)
3.9 mm
Useful cross section (EF005140)
3500 mm²
Integrated partition (EF004799)
None
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 304 (1.4301)
Surface protection (EF000139)
Untreated
Weight (EF000167)
0.49 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1 m

Safe working load according to IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 35 100 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.