

INDUSTRIAL COMPONENT DATA

GRM 35 200 A4 6000090 OBO BETTERMANN Mesh cable tray

GRM , 35x200x3000, Stainless steel, grade 316, VA, 1.44..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 35 200 A4



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 35 200 A4
Catalog number	6000090
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-C5E7D61DDE
Generated	2026-07-29

Product Overview

Mesh cable tray GRM , 35x200x3000, Stainless steel, grade 316, VA, 1.4401
 GRM GRM 35 200 A4 grid tray, 35x200x3000 Stainless steel 1.4401, V4A, 1.4401, Polished, with post-treatment
 GR-Magic® 35 A4 Grid Tray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid
--------------	--

Additional Product Information

No additional connection components are required for the mesh cable tray, it is simply interlocked. The grid width is 50 x 100 mm (exception: GRM 35/50 = 20 x 100 mm).

ETIM for 6000090 Cable tray, ladder and wire basket systems (EC000853)

Feature Name

Feature Value

Profile shape (EF005179)

U-shape

Width (EF000008)

200 mm

Height (EF000040)

35 mm

Length (EF001438)

3000 mm

Diameter longitudinal wire (EF017247)

3.9 mm

Diameter transverse wire (EF017380)

3.9 mm

Useful cross section (EF005140)

7000 mm²

Integrated partition (EF004799)

None

Model (EF000010)

Integrated coupler

Type of connector (EF000141)

Click in

Suitable for circuit integrity (EF007806)

No

Material (EF002169)

Stainless steel

Material quality (EF001257)

Stainless steel 316 (1.4401)

Surface protection (EF000139)

Untreated

Weight (EF000167)

0.76 kg/m

Load test type according to IEC 61537 (EF015362)

Type II

Possible support spacing (EF017261)

1 m

Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)

300

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)

140

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)

100

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 35 200 A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.