


INDUSTRIAL COMPONENT DATA

GRM 35 300 FT 6000075 OBO BETTERMANN Mesh cable tray

GRM , 35x300x3000, Hot-dip galvanised, DIN EN ISO 1461,..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 35 300 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 35 300 FT
Catalog number	6000075
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-5D2BBE63D6
Generated	2026-08-01

Product Overview

Mesh cable tray GRM , 35x300x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
GRM GRM 35 300 FT Grid Tray, 35x300x3000 Steel, St, Hot Dip Galvanized, DIN EN ISO 1461
Mesh cable tray GR-Magic® 35 FT. Mesh cable tray with shaped connector of side height 35 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 3,3754 kg CO2e / 1 Meter
Colour zinc
Connector version Integrated connector
Dimension 35x300x3000
Dimension B 300 mm
Height 1,38 in
Height 35 mm
Integrated partition Without
Length 3000 mm
Load test type according to IEC 61537 Type II
Maintain electrical functions no
Material Steel

Profile shape U-shaped
Rustproof steel, pickled no
Screwless connector yes
Support spacing 1.0 m 0,75 kN/m
Support spacing 1.5 m 0,22 kN/m
Support spacing 2.0 m 0,15 kN/m
Surface Hot-dip galvanised
Type of connector, cable support system Click fastening
Usable cross-section 10500 mm²
Usable cross-section 71,3 cm²
Wide-span version no
Width 300 mm
Width 11,81 in
Wire diameter 4,8 mm
ETIM for 6000075 Cable tray, ladder and wire basket systems (EC000853)
Feature Name
Feature Value
Profile shape (EF005179)
U-shape
Width (EF000008)
300 mm
Height (EF000040)
35 mm
Length (EF001438)
3000 mm
Diameter longitudinal wire (EF017247)
4.8 mm
Diameter transverse wire (EF017380)
4.8 mm
Useful cross section (EF005140)
10500 mm²
Integrated partition (EF004799)
None
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Hot dip galvanized
Weight (EF000167)
1.65 kg/m
Load test type according to IEC 61537 (EF015362)
Type II

Possible support spacing (EF017261)

1 m

Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)

750

Safe working load acco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 35 300 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.