

**INDUSTRIAL COMPONENT DATA**

# GRM 55 100VA4401 6001088 OBO BETTERMANN Mesh cable tray GRM , 55x100x3000, Stained, Stainless steel, grade 3..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 55 100 A4



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | GRM 55 100 A4   |
| Catalog number  | 6001088         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-18B156B942   |
| Generated       | 2026-08-02      |

## Product Overview

Mesh cable tray GRM , 55x100x3000, Stained, Stainless steel, grade 316, VA, 1.4401

Mesh cable tray GR-Magic® 55 A4. Mesh cable tray with shaped connector of side height 55 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid |
|--------------|--------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 3,6441 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 55x100x3000

Dimension B 100 mm

Dimension H 58 mm

Fire protection Maintenance of electrical function of cable-specific support structure

Height 55 mm

Height 2,17 in

Integrated partition Without

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions yes

Material Stainless steel 1.4401  
Profile shape U-shaped  
Rustproof steel, pickled yes  
Screwless connector yes  
Support spacing 1.0 m 0,35 kN/m  
Support spacing 1.5 m 0,2 kN/m  
Support spacing 2.0 m 0,1 kN/m  
Support spacing 2.5 m 0,1 kN/m  
Surface Bright, treated  
Type of connector, cable support system Click fastening  
Usable cross-section 40 cm<sup>2</sup>  
Usable cross-section 4000 mm<sup>2</sup>  
Wide-span version no  
Width 100 mm  
Width 3,94 in  
Wire diameter 3,9 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 55 100 A4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.