

INDUSTRIAL COMPONENT DATA

GRM 55 200 A2 6001076 OBO BETTERMANN Mesh cable tray

GRM , 55x200x3000, Stained, Stainless steel, grade 304,..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 55 200 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 55 200 A2
Catalog number	6001076
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-2B00947103
Generated	2026-08-02

Product Overview

Mesh cable tray GRM , 55x200x3000, Stained, Stainless steel, grade 304, VA, 1.4301

GRM GRM 55 200 A2 Grid Tray, 55x200x3000 Stainless Steel 1.4301, A2, 1.4301, Polished, with Post Treatment

GR-Magic® 55 A2 grid tray. Grid tray with quick flange connection 55 mm. Magnetic insulation without lid 15 dB, with lid 25 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid
--------------	--

Additional Product Information

No additional connection components are required for the mesh cable tray, it is simply interlocked. The grid width is 50 x 100 mm (exception: GRM 55/50 = 20 x 100 mm).

ETIM for 6001076 Cable tray, ladder and wire basket systems (EC000853)

Feature Name

Feature Value

Profile shape (EF005179)

U-shape

Width (EF000008)

200 mm

Height (EF000040)

55 mm

Length (EF001438)

3000 mm
Diameter longitudinal wire (EF017247)
3.9 mm
Diameter transverse wire (EF017380)
3.9 mm
Useful cross section (EF005140)
8700 mm²
Integrated partition (EF004799)
None
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
Yes
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 304 (1.4301)
Surface protection (EF000139)
Untreated
Weight (EF000167)
0.99 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1 m
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)
350
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
200
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
100
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
100

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 55 200 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.