


INDUSTRIAL COMPONENT DATA

GRM 55 600 G 6001454 OBO BETTERMANN Mesh cable tray

GRM , 55x600x3000, Electrogalvanised, DIN 50961, Steel, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 55 600 G



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 55 600 G
Catalog number	6001454
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-5AD792D484
Generated	2026-07-29

Product Overview

Mesh cable tray GRM , 55x600x3000, Electrogalvanised, DIN 50961, Steel, St
GRM GRM 55 600 G grid tray, 55x600x3000 Steel, St, electro-galvanized, EN ISO 19598 / EN ISO 4042
GR-Magic® 55 G grid tray. Grid tray with quick connection with 55 mm wing. Magnetic insulation without lid 15 dB, with lid 25 dB. You can consult more accurate information about the UL classification in the corresponding approval.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid

Additional Product Information

Magnetic shield insulation without cover 15 dB, with cover 25 dB. You can find detailed information regarding the UL classification in the respective certification.

ETIM for 6001454 Cable tray, ladder and wire basket systems (EC000853)

Feature Name

Feature Value

Profile shape (EF005179)

U-shape

Width (EF000008)

600 mm

Height (EF000040)

55 mm

Length (EF001438)

3000 mm
Diameter longitudinal wire (EF017247)
4.8 mm
Diameter transverse wire (EF017380)
4.8 mm
Useful cross section (EF005140)
26500 mm²
Integrated partition (EF004799)
None
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Steel
Surface protection (EF000139)
Galvanic/electrolytic zinc plated
Weight (EF000167)
3.2 kg/m
Load test type according to IEC 61537 (EF015362)
Type II
Possible support spacing (EF017261)
1 m
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)
900
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
600
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
300
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
250

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 55 600 G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.