


**INDUSTRIAL COMPONENT DATA**

# GRM 55 600 G 6001454 OBO BETTERMANN Mesh cable tray

## GRM , 55x600x3000, Electrogalvanised, DIN 50961, Steel, ..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 55 600 G



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | GRM 55 600 G    |
| Catalog number  | 6001454         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-5AD792D484   |
| Generated       | 2026-08-01      |

### Product Overview

Mesh cable tray GRM , 55x600x3000, Electrogalvanised, DIN 50961, Steel, St  
GRM GRM 55 600 G grid tray, 55x600x3000 Steel, St, electro-galvanized, EN ISO 19598 / EN ISO 4042  
GR-Magic® 55 G grid tray. Grid tray with quick connection with 55 mm wing. Magnetic insulation without lid 15 dB, with lid 25 dB. You can consult more accurate information about the UL classification in the corresponding approval.

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Grid

### Additional Product Information

Magnetic shield insulation without cover 15 dB, with cover 25 dB. You can find detailed information regarding the UL classification in the respective certification.

ETIM for 6001454 Cable tray, ladder and wire basket systems (EC000853)

Feature Name

Feature Value

Profile shape (EF005179)

U-shape

Width (EF000008)

600 mm

Height (EF000040)

55 mm

Length (EF001438)

3000 mm  
Diameter longitudinal wire (EF017247)  
4.8 mm  
Diameter transverse wire (EF017380)  
4.8 mm  
Useful cross section (EF005140)  
26500 mm<sup>2</sup>  
Integrated partition (EF004799)  
None  
Model (EF000010)  
Integrated coupler  
Type of connector (EF000141)  
Click in  
Suitable for circuit integrity (EF007806)  
No  
Material (EF002169)  
Steel  
Surface protection (EF000139)  
Galvanic/electrolytic zinc plated  
Weight (EF000167)  
3.2 kg/m  
Load test type according to IEC 61537 (EF015362)  
Type II  
Possible support spacing (EF017261)  
1 m  
Safe working load according to IEC 61537 with support spacing 1.0 m (EF017263)  
900  
Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)  
600  
Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)  
300  
Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)  
250

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 55 600 G with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.