

**INDUSTRIAL COMPONENT DATA**

# GRM105 100VA4301 6002451 OBO BETTERMANN Mesh cable tray GRM , 105x100x3000, Stained, Stainless steel, grade ..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 105 100 A2



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | GRM 105 100 A2  |
| Catalog number  | 6002451         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-6964FEA690   |
| Generated       | 2026-07-31      |

## Product Overview

Mesh cable tray GRM , 105x100x3000, Stained, Stainless steel, grade 304, VA, 1.4301

Mesh cable tray GR-Magic® 105 A2. Mesh cable tray with shaped connector of side height 105 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid |
|--------------|--------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 5,0002 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 105x100x3000

Dimension B 100 mm

Dimension H 108 mm

Height 105 mm

Height 4,13 in

Integrated partition Without

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Stainless steel 1.4301

Profile shape U-shaped  
Rustproof steel, pickled yes  
Screwless connector yes  
Support spacing 1.0 m 0,8 kN/m  
Support spacing 1.5 m 0,55 kN/m  
Support spacing 2.0 m 0,37 kN/m  
Support spacing 2.5 m 0,27 kN/m  
Support spacing 3.0 m 0,25 kN/m  
Surface Bright, treated  
Type of connector, cable support system Click fastening  
Usable cross-section 82 cm<sup>2</sup>  
Usable cross-section 8200 mm<sup>2</sup>  
Wide-span version no  
Width 100 mm  
Width 3,94 in  
Wire diameter 3,9 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 105 100 A2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.