

INDUSTRIAL COMPONENT DATA

GRM 105 200 A4 6002477 OBO BETTERMANN Mesh cable tray

GRM , 105x200x3000, Stained, Stainless steel, grade 31..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 105 200 A4



Manufacturer	OBO BETTERMANN
MPN / Reference	GRM 105 200 A4
Catalog number	6002477
Category	Mesh cable tray
Minimum order	3 m.
Document ID	EO-82F62625EB
Generated	2026-07-29

Product Overview

Mesh cable tray GRM , 105x200x3000, Stained, Stainless steel, grade 316, VA, 1.4401

GRM GRM 105 200 A4 Grid Tray, 105x200x3000 Stainless Steel 1.4401, V4A, 1.4401, Polished, with Post Treatment

Mesh cable tray GR-Magic® 105 A4. Mesh cable tray with shaped connector of side height 105 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid
--------------	--

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 9,7733 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 105x200x3000

Dimension B 200 mm

Dimension H 108 mm

Height 4,13 in

Height 105 mm

Integrated partition Without

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Stainless steel 1.4401
Profile shape U-shaped
Rustproof steel, pickled yes
Screwless connector yes
Support spacing 1.0 m 0,8 kN/m
Support spacing 1.5 m 0,55 kN/m
Support spacing 2.0 m 0,37 kN/m
Support spacing 2.5 m 0,27 kN/m
Support spacing 3.0 m 0,25 kN/m
Surface Bright, treated
Type of connector, cable support system Click fastening
Usable cross-section 17500 mm²
Usable cross-section 175 cm²
Wide-span version no
Width 7,87 in
Width 200 mm
Wire diameter 4,8 mm
ETIM for 6002477 Cable tray, ladder and wire basket systems (EC000853)
Feature Name
Feature Value
Profile shape (EF005179)
U-shape
Width (EF000008)
200 mm
Height (EF000040)
105 mm
Length (EF001438)
3000 mm
Diameter longitudinal wire (EF017247)
4.8 mm
Diameter transverse wire (EF017380)
4.8 mm
Useful cross section (EF005140)
17500 mm²
Integrated partition (EF004799)
None
Model (EF000010)
Integrated coupler
Type of connector (EF000141)
Click in
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)
Stainless steel 316 (1.4401)
Surface protection (EF000139)

Untreated

Weight (EF000167)

1.92 kg/m

Load test type according to IEC 615...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 105 200 A4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.