


**INDUSTRIAL COMPONENT DATA**

# GRM 105 200 A4 6002477 OBO BETTERMANN Mesh cable tray

## GRM , 105x200x3000, Stained, Stainless steel, grade 31..

Brand: OBO BETTERMANN | Manufacturer Part Number: GRM 105 200 A4



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | OBO BETTERMANN  |
| MPN / Reference | GRM 105 200 A4  |
| Catalog number  | 6002477         |
| Category        | Mesh cable tray |
| Minimum order   | 3 m.            |
| Document ID     | EO-82F62625EB   |
| Generated       | 2026-08-01      |

### Product Overview

Mesh cable tray GRM , 105x200x3000, Stained, Stainless steel, grade 316, VA, 1.4401

GRM GRM 105 200 A4 Grid Tray, 105x200x3000 Stainless Steel 1.4401, V4A, 1.4401, Polished, with Post Treatment

Mesh cable tray GR-Magic® 105 A4. Mesh cable tray with shaped connector of side height 105 mm. Magnetic shield insulation without cover 15 dB, with cover 25 dB.

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Grid |
|--------------|--------------------------------------------------------------------|

### Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 9,7733 kg CO2e / 1 Meter

Colour stainless steel

Connector version Integrated connector

Dimension 105x200x3000

Dimension B 200 mm

Dimension H 108 mm

Height 4,13 in

Height 105 mm

Integrated partition Without

Length 3000 mm

Load test type according to IEC 61537 Type II

Maintain electrical functions no

Material Stainless steel 1.4401  
Profile shape U-shaped  
Rustproof steel, pickled yes  
Screwless connector yes  
Support spacing 1.0 m 0,8 kN/m  
Support spacing 1.5 m 0,55 kN/m  
Support spacing 2.0 m 0,37 kN/m  
Support spacing 2.5 m 0,27 kN/m  
Support spacing 3.0 m 0,25 kN/m  
Surface Bright, treated  
Type of connector, cable support system Click fastening  
Usable cross-section 17500 mm<sup>2</sup>  
Usable cross-section 175 cm<sup>2</sup>  
Wide-span version no  
Width 7,87 in  
Width 200 mm  
Wire diameter 4,8 mm  
ETIM for 6002477 Cable tray, ladder and wire basket systems (EC000853)  
Feature Name  
Feature Value  
Profile shape (EF005179)  
U-shape  
Width (EF000008)  
200 mm  
Height (EF000040)  
105 mm  
Length (EF001438)  
3000 mm  
Diameter longitudinal wire (EF017247)  
4.8 mm  
Diameter transverse wire (EF017380)  
4.8 mm  
Useful cross section (EF005140)  
17500 mm<sup>2</sup>  
Integrated partition (EF004799)  
None  
Model (EF000010)  
Integrated coupler  
Type of connector (EF000141)  
Click in  
Suitable for circuit integrity (EF007806)  
No  
Material (EF002169)  
Stainless steel  
Material quality (EF001257)  
Stainless steel 316 (1.4401)  
Surface protection (EF000139)

Untreated

Weight (EF000167)

1.92 kg/m

Load test type according to IEC 615...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / GRM 105 200 A4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.