

**INDUSTRIAL COMPONENT DATA**

# LG 113 VS 3 FS 6216407 OBO BETTERMANN Cable ladder perforated, with VS rungs, 110x300x3000, Strip-galvanised..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 113 VS 3 FS



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | LG 113 VS 3 FS                      |
| Catalog number  | 6216407                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 3 m.                                |
| Document ID     | EO-B096B2F951                       |
| Generated       | 2026-08-01                          |

## Product Overview

Cable ladder perforated, with VS rungs, 110x300x3000, Strip-galvanised, DIN EN 10147, Steel, St  
Cable ladder LG 110, 3 m VS FS. Cable ladder with perforated side rail of side height 110 mm with riveted C profile rungs, open in an upwards direction. Magnetic shield insulation without cover 10 dB, with cover 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray |
|--------------|---------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 9,6084 kg CO2e / 1 Meter

Colour zinc

Dimension 110x300x3000

Dimension 110x300x3000

Dimension B 300 mm

Fastening of rung Blind riveted

Height 110 mm

Length 3000 mm

Maintain electrical functions no

Material Steel

Rail thickness 1,5 mm

Rung distance 300 mm

Rung slot dimension 16,50

Rustproof steel, pickled no  
Side perforation yes  
Side rail version Flat profile  
Support spacing 2.0 m 3,1 kN/m  
Support spacing 2.5 m 2 kN/m  
Support spacing 3.0 m 1,4 kN/m  
Support spacing 3.5 m 0,9 kN/m  
Support spacing 4.0 m 0,65 kN/m  
Support spacing 4.5 m 0,55 kN/m  
Support spacing 5.0 m 0,5 kN/m  
Support spacing 6.0 m 0,15 kN/m  
Surface Strip galvanized  
Usable cross-section 283 cm<sup>2</sup>  
Usable cross-section 28300 mm<sup>2</sup>  
Version of the rungs Profile perforated  
Wide-span version no  
Width 300 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 113 VS 3 FS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.