

INDUSTRIAL COMPONENT DATA

LG 114 VS 3 FT 6216429 OBO BETTERMANN Cable ladder perforated, with VS rungs, 110x400x3000, Hot-dip galvanis..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 114 VS 3 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 114 VS 3 FT
Catalog number	6216429
Category	Cable ladder/wide span cable ladder
Minimum order	3 m.
Document ID	EO-8B0955256E
Generated	2026-08-01

Product Overview

Cable ladder perforated, with VS rungs, 110x400x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
 LG 114 VS 3 FT stair tray, perforated, with step VS 110x400x3000 Steel, St, Hot dip galvanized, DIN EN ISO 1461
 Cable ladder LG 110, 3 m VS FT. Cable ladder with perforated side rail of side height 110 mm with riveted C profile rungs, open in an upwards direction. Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 9,9171 kg CO2e / 1 Meter
 Colour zinc
 Dimension 110x400x3000
 Dimension 110x400x3000
 Dimension B 400 mm
 Fastening of rung Blind riveted
 Height 110 mm
 Length 3000 mm
 Maintain electrical functions no
 Material Steel
 Rail thickness 1,5 mm
 Rung distance 300 mm

Rung slot dimension 16,50
Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 2.0 m 3,1 kN/m
Support spacing 2.5 m 2 kN/m
Support spacing 3.0 m 1,4 kN/m
Support spacing 3.5 m 0,9 kN/m
Support spacing 4.0 m 0,65 kN/m
Support spacing 4.5 m 0,55 kN/m
Support spacing 5.0 m 0,5 kN/m
Support spacing 6.0 m 0,15 kN/m
Surface Hot-dip galvanised
Usable cross-section 37800 mm²
Usable cross-section 378 cm²
Version of the rungs Profile perforated
Wide-span version no
Width 400 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 114 VS 3 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.