

INDUSTRIAL COMPONENT DATA

LG 115 VS 3 FT 6216432 OBO BETTERMANN Cable ladder perforated, with VS rungs, 110x500x3000, Hot-dip galvanis..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 115 VS 3 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 115 VS 3 FT
Catalog number	6216432
Category	Cable ladder/wide span cable ladder
Minimum order	3 m.
Document ID	EO-1854DF2DE3
Generated	2026-08-03

Product Overview

Cable ladder perforated, with VS rungs, 110x500x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St Cable ladder LG 110, 3 m VS FT. Cable ladder with perforated side rail of side height 110 mm with riveted C profile rungs, open in an upwards direction. Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 10,4622 kg CO2e / 1 Meter

Colour zinc

Dimension 110x500x3000

Dimension 110x500x3000

Dimension B 500 mm

Fastening of rung Blind riveted

Height 110 mm

Length 3000 mm

Maintain electrical functions no

Material Steel

Rail thickness 1,5 mm

Rung distance 300 mm

Rung slot dimension 16,50

Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 2.0 m 3,1 kN/m
Support spacing 2.5 m 2 kN/m
Support spacing 3.0 m 1,4 kN/m
Support spacing 3.5 m 0,9 kN/m
Support spacing 4.0 m 0,65 kN/m
Support spacing 4.5 m 0,55 kN/m
Support spacing 5.0 m 0,5 kN/m
Support spacing 6.0 m 0,15 kN/m
Surface Hot-dip galvanised
Usable cross-section 475 cm²
Usable cross-section 47500 mm²
Version of the rungs Profile perforated
Wide-span version no
Width 500 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 115 VS 3 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.