

**INDUSTRIAL COMPONENT DATA**

# LG 620 VS 3 FT 6208562 OBO BETTERMANN Cable ladder perforated, with VS rungs, 60x200x3000, Hot-dip galvanise..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 620 VS 3 FT



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | LG 620 VS 3 FT                      |
| Catalog number  | 6208562                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 3 m.                                |
| Document ID     | EO-04FB898770                       |
| Generated       | 2026-08-01                          |

## Product Overview

Cable ladder perforated, with VS rungs, 60x200x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St Cable ladder LG 60, 3 m VS FT. Cable ladder with perforated side rail of side height 60 mm with riveted C profile frames, open in an upwards direction (VS version).Magnetic shield insulation without cover 10 dB, with cover 15 dB.Additional widths are available on request.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray |
|--------------|---------------------------------------------------------------------------|

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 6,2603 kg CO2e / 1 Meter  
Colour zinc  
Dimension 60x200x3000  
Dimension B 200 mm  
Fastening of rung Blind riveted  
Fire protection Maintenance of electrical function of standard support structure  
Height 60 mm  
Length 3000 mm  
Maintain electrical functions yes  
Material Steel  
Rail thickness 1,5 mm  
Rung distance 300 mm

Rung slot dimension 16,50  
Rustproof steel, pickled no  
Side perforation yes  
Side rail version Flat profile  
Support spacing 1.5 m 3,1 kN/m  
Support spacing 2.0 m 2,25 kN/m  
Support spacing 2.5 m 1,5 kN/m  
Support spacing 3.0 m 1,1 kN/m  
Support spacing 3.5 m 0,75 kN/m  
Support spacing 4.0 m 0,45 kN/m  
Support spacing 4.5 m 0,3 kN/m  
Support spacing 5.0 m 0,15 kN/m  
Surface Hot-dip galvanised  
Usable cross-section 9800 mm<sup>2</sup>  
Usable cross-section 98 cm<sup>2</sup>  
Version of the rungs Profile perforated  
Wide-span version no  
Width 200 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 620 VS 3 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.