

INDUSTRIAL COMPONENT DATA

LG 630 VS 3 FS 6208541 OBO BETTERMANN Cable ladder perforated, with VS rungs, 60x300x3000, Strip-galvanised,..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 630 VS 3 FS



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 630 VS 3 FS
Catalog number	6208541
Category	Cable ladder/wide span cable ladder
Minimum order	3 m.
Document ID	EO-D4E77E8225
Generated	2026-08-01

Product Overview

Cable ladder perforated, with VS rungs, 60x300x3000, Strip-galvanised, DIN EN 10147, Steel, St
Cable ladder LG 60, 3 m VS FS. Cable ladder with perforated side rail of side height 60 mm with riveted C profile frames, open in an upwards direction (VS version).Magnetic shield insulation without cover 10 dB, with cover 15 dB.Additional widths are available on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 6,9591 kg CO2e / 1 Meter
Colour zinc
Dimension 60x300x3000
Dimension 60x300x3000
Dimension B 300 mm
Fastening of rung Blind riveted
Fire protection Maintenance of electrical function of standard support structure
Height 60 mm
Length 3000 mm
Maintain electrical functions yes
Material Steel
Rail thickness 1,5 mm

Rung distance 300 mm
Rung slot dimension 16,50
Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 1.5 m 3,1 kN/m
Support spacing 2.0 m 2,25 kN/m
Support spacing 2.5 m 1,5 kN/m
Support spacing 3.0 m 1,1 kN/m
Support spacing 3.5 m 0,75 kN/m
Support spacing 4.0 m 0,45 kN/m
Support spacing 4.5 m 0,3 kN/m
Support spacing 5.0 m 0,15 kN/m
Surface Strip galvanized
Usable cross-section 14800 mm²
Usable cross-section 148 cm²
Version of the rungs Profile perforated
Wide-span version no
Width 300 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 630 VS 3 FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.