


**INDUSTRIAL COMPONENT DATA**

# LG 630 VS6VA4301 6208703 OBO BETTERMANN Cable ladder perforated, with VS rungs, 60x300x6000, Stainless steel..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 630 VS6 A2



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | OBO BETTERMANN                      |
| MPN / Reference | LG 630 VS6 A2                       |
| Catalog number  | 6208703                             |
| Category        | Cable ladder/wide span cable ladder |
| Minimum order   | 6 m.                                |
| Document ID     | EO-9378FE7ED6                       |
| Generated       | 2026-08-03                          |

## Product Overview

Cable ladder perforated, with VS rungs, 60x300x6000, Stainless steel, grade 304, VA, 1.4301

Cable ladder LG 60, 6 m VS A2. Cable ladder with perforated side rail of side height 60 mm with riveted C profile frames, open in an upwards direction (VS version).Magnetic shield insulation without cover 10 dB, with cover 15 dB.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      OBO BETTERMANN &gt; KTS cable support systems - OBO BETTERMANN &gt; Ladder Tray

## Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 14,8096 kg CO2e / 1 Meter

Colour stainless steel

Dimension 60x300x6000

Dimension 60x300x6000

Dimension B 300 mm

Fastening of rung Blind riveted

Height 60 mm

Length 6000 mm

Maintain electrical functions no

Material Stainless steel 1.4301

Rail thickness 1,5 mm

Rung distance 300 mm

Rung slot dimension 16,50

Rustproof steel, pickled no  
Side perforation yes  
Side rail version Flat profile  
Support spacing 1.5 m 3,1 kN/m  
Support spacing 2.0 m 2,25 kN/m  
Support spacing 2.5 m 1,5 kN/m  
Support spacing 3.0 m 1,1 kN/m  
Support spacing 3.5 m 0,75 kN/m  
Support spacing 4.0 m 0,45 kN/m  
Support spacing 4.5 m 0,3 kN/m  
Support spacing 5.0 m 0,15 kN/m  
Surface Bright, treated  
Usable cross-section 14800 mm<sup>2</sup>  
Usable cross-section 148 cm<sup>2</sup>  
Version of the rungs Profile perforated  
Wide-span version no  
Width 300 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 630 VS6 A2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.