

INDUSTRIAL COMPONENT DATA

LG 640 VS 3 FT 6208570 OBO BETTERMANN Cable ladder perforated, with VS rungs, 60x400x3000, Hot-dip galvanise..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 640 VS 3 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 640 VS 3 FT
Catalog number	6208570
Category	Cable ladder/wide span cable ladder
Minimum order	3 m.
Document ID	EO-A9C91AAFC1
Generated	2026-08-03

Product Overview

Cable ladder perforated, with VS rungs, 60x400x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St Cable ladder LG 60, 3 m VS FT. Cable ladder with perforated side rail of side height 60 mm with riveted C profile frames, open in an upwards direction (VS version).Magnetic shield insulation without cover 10 dB, with cover 15 dB.Additional widths are available on request.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray
--------------	---

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 7,4073 kg CO2e / 1 Meter
Colour zinc
Dimension 60x400x3000
Dimension B 400 mm
Fastening of rung Blind riveted
Fire protection Maintenance of electrical function of standard support structure
Height 60 mm
Length 3000 mm
Maintain electrical functions yes
Material Steel
Rail thickness 1,5 mm
Rung distance 300 mm

Rung slot dimension 16,50
Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 1.5 m 3,1 kN/m
Support spacing 2.0 m 2,25 kN/m
Support spacing 2.5 m 1,5 kN/m
Support spacing 3.0 m 1,1 kN/m
Support spacing 3.5 m 0,75 kN/m
Support spacing 4.0 m 0,45 kN/m
Support spacing 4.5 m 0,3 kN/m
Support spacing 5.0 m 0,15 kN/m
Surface Hot-dip galvanised
Usable cross-section 198 cm²
Usable cross-section 19800 mm²
Version of the rungs Profile perforated
Wide-span version no
Width 400 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 640 VS 3 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.