


INDUSTRIAL COMPONENT DATA

LG 650 VS6 A4 6101223 OBO BETTERMANN Cable ladder perforated, with VS rungs, 60x500x6000, Stainless steel, g..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 650 VS6VA4571



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 650 VS6VA4571
Catalog number	6101223
Category	Cable ladder/wide span cable ladder
Minimum order	6 Pcs
Document ID	EO-A3D3AC4DF8
Generated	2026-08-03

Product Overview

Cable ladder perforated, with VS rungs, 60x500x6000, Stainless steel, grade 316 Ti, VA, 1.4571

LG 650 VS6 A4 Perforated Stair Tray, with VS 60x500x6000 Stainless Steel Step Stainless Steel 1.4571, V4A, 1.4571
 Polished, with Post Treatment

Cable ladder LG 60, 6 m VS A4. Cable ladder with perforated side rail of side height 60 mm with riveted C profile frames, open in an upwards direction (VS version).Magnetic shield insulation without cover 10 dB, with cover 15 dB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray

Additional Product Information

CO2 Footprint (GWP) Cradle-to-Gate 17,2807 kg CO2e / 1 Meter

Colour stainless steel

Dimension 60x500x6000

Dimension 60x500x6000

Dimension B 500 mm

Fastening of rung Blind riveted

Height 60 mm

Length 6000 mm

Maintain electrical functions no

Material Stainless steel 1.4571

Rail thickness 1,5 mm

Rung distance 300 mm
Rung slot dimension 16,50
Rustproof steel, pickled no
Side perforation yes
Side rail version Flat profile
Support spacing 1.5 m 3,1 kN/m
Support spacing 2.0 m 2,25 kN/m
Support spacing 2.5 m 1,5 kN/m
Support spacing 3.0 m 1,1 kN/m
Support spacing 3.5 m 0,75 kN/m
Support spacing 4.0 m 0,45 kN/m
Support spacing 4.5 m 0,3 kN/m
Support spacing 5.0 m 0,15 kN/m
Surface Bright, treated
Usable cross-section 248 cm²
Usable cross-section 24800 mm²
Version of the rungs Profile perforated
Wide-span version no
Width 500 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 650 VS6VA4571 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.