

INDUSTRIAL COMPONENT DATA

LG 660 VS 3 FT 6208578 OBO BETTERMANN Cable ladder perforated, with VS rungs, 60x600x3000, Hot-dip galvanise..

Brand: OBO BETTERMANN | Manufacturer Part Number: LG 660 VS 3 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	LG 660 VS 3 FT
Catalog number	6208578
Category	Cable ladder/wide span cable ladder
Minimum order	3 m.
Document ID	EO-1EEF8184D9
Generated	2026-08-03

Product Overview

Cable ladder perforated, with VS rungs, 60x600x3000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
 LG 660 VS 3 FT ladder tray, perforated, with step VS 60x600x3000 Steel, St, hot-dip galvanized, DIN EN ISO 1461
 Cable ladder LG 60, 3 m VS FT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > Ladder Tray
--------------	---

Additional Product Information

The cable ladder is shipped folded up.
 You can find the appropriate clamp clip of type 2056 in the Ladder systems section.
 ETIM for 6208578 Cable tray, ladder and wire basket systems (EC000854)
 Feature Name
 Feature Value
 Type of side joist (EF007666)
 Flat profile
 Side perforation (EF001122)
 Yes
 Type of rung (EF001060)
 Slotted channel
 Fixation rung (EF008307)
 Blind riveted

Height (EF000040)
60 mm

Width (EF000008)
600 mm

Length (EF001438)
3000 mm

Useful cross section (EF005140)
29800 mm²

Suitable for circuit integrity (EF007806)
No

Rung centre spacing (EF008185)
300 mm

Vertical cable ladder (EF017249)
Yes

Material (EF002169)
Steel

Surface protection (EF000139)
Hot dip galvanized

Weight (EF000167)
3.85 kg/m

Possible support spacing (EF017261)
1.5 m

Safe working load according to IEC 61537 with support spacing 1.5 m (EF017264)
3100

Safe working load according to IEC 61537 with support spacing 2.0 m (EF017265)
2250

Safe working load according to IEC 61537 with support spacing 2.5 m (EF017266)
1500

Safe working load according to IEC 61537 with support spacing 3.0 m (EF017267)
1100

Safe working load according to IEC 61537 with support spacing 4.0 m (EF017268)
450

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / LG 660 VS 3 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.