

INDUSTRIAL COMPONENT DATA

IS 8 110 FT 6337120 OBO BETTERMANN I support , 80x42x1100, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

Brand: OBO BETTERMANN | Manufacturer Part Number: IS 8 110 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	IS 8 110 FT
Catalog number	6337120
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-772D262078
Generated	2026-07-28

Product Overview

I support , 80x42x1100, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
IS 8 support. I support in fixed lengths. Dimensions 80 x 42 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories

Additional Product Information

Breakable no
CO2 Footprint (GWP) Cradle-to-Gate 14,4317 kg CO2e / 1 Piece
Colour zinc
Dimension 80 x 42
Dimension 80x42x1100
EPD article yes
Height 42 mm
Hole width 14 mm
Length 1100 mm
Maintain electrical functions no
Material Steel
Material thickness 4 mm
Profile shape I profile
Slot width 70 mm

Static value A 7,02 cm²
Static value I_y 6,26 cm⁴
Static value I_z 77,53 cm⁴
Static value W_y 2,98 cm³
Static value W_z 19,38 cm³
Surface Hot-dip galvanised
Type of perforation Perforated bar
Version for Single profile
Width 80 mm
With toothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / IS 8 110 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.