

INDUSTRIAL COMPONENT DATA

US 3 200 VA4571 6342497 OBO BETTERMANN U support 3-sided perforated, 50x30x2000, Stained, Stainless steel, g..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 3 200 VA4571



Manufacturer	OBO BETTERMANN
MPN / Reference	US 3 200 VA4571
Catalog number	6342497
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-62F68E6B50
Generated	2026-07-28

Product Overview

U support 3-sided perforated, 50x30x2000, Stained, Stainless steel, grade 316 Ti, VA, 1.4571

US 3 support A4. U support in fixed lengths. Dimensions 30 x 50 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories
--------------	--

Additional Product Information

Breakable no

CO2 Footprint (GWP) Cradle-to-Gate 15,593 kg CO2e / 1 Piece

Colour stainless steel

Dimension 30 x 50 x 2,0

Dimension 50x30x2000

Height 30 mm

Length 2000 mm

Maintain electrical functions no

Material Stainless steel 1.4571

Material thickness 2 mm

Profile shape U profile

Static value A 1,42 cm²

Static value Iy 1,52 cm⁴

Static value Iz 5,72 cm⁴

Static value Wy 0,7 cm³

Static value Wz 2,29 cm³

Surface Bright, treated

Type of perforation 3 sides perforated

Version for Single profile

Width 50 mm

With toothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 3 200 VA4571 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.