

INDUSTRIAL COMPONENT DATA

US 3 600 A2 6342468 OBO BETTERMANN U support 3-sided perforated, 50x30x6000, Stained, Stainless steel, grade..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 3 600 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	US 3 600 A2
Catalog number	6342468
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-C86C08FEF3
Generated	2026-07-29

Product Overview

U support 3-sided perforated, 50x30x6000, Stained, Stainless steel, grade 304, VA, 1.4301

U-Profile US 3 600 A2, 3-sided perforated 50x30x6000 Stainless steel 1.4301, A2, 1.4301, Polished, post-treated

US 3 support A2. U support in fixed lengths. Dimensions 30 x 50 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories

Additional Product Information

Breakable no

CO2 Footprint (GWP) Cradle-to-Gate 46,6487 kg CO2e / 1 Piece

Colour stainless steel

Dimension 30 x 50 x 2,0

Dimension 50x30x6000

Height 30 mm

Length 6000 mm

Maintain electrical functions no

Material Stainless steel 1.4301

Material thickness 2 mm

Profile shape U profile

Static value A 1,42 cm²

Static value Iy 1,52 cm⁴

Static value Iz 5,72 cm⁴
Static value Wy 0,7 cm³
Static value Wz 2,29 cm³
Surface Bright, treated
Type of perforation 3 sides perforated
Version for Single profile
Width 50 mm
With toothing no
ETIM for 6342468 Fixings and fasteners (EC000386)
Feature Name
Feature Value
Length (EF001438)
6000 mm
Width (EF000008)
50 mm
Height (EF000040)
30 mm
Material thickness (EF000386)
2 mm
Profile shape (EF005179)
U-profile
Type of perforation (EF004147)
3 sides perforated
With toothing (EF000571)
No
Area moment of inertia Iy (EF012513)
1.52 cm⁴
Area of inertia Iz (EF012514)
5.72 cm⁴
Moment of resistance Wy (EF012503)
0.7 cm³
Moment of resistance Wz (EF012504)
2.29 cm³
Suitable for circuit integrity (EF007806)
No
Material (EF002169)
Stainless steel
Material quality (EF001257)
Rustproof and acidproof steel
Surface protection (EF000139)
Other
Weight (EF000167)
7.9 kg

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 3 600 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.