

INDUSTRIAL COMPONENT DATA

US 5 200 FT 6340970 OBO BETTERMANN U support 3-sided perforated, 50x50x2000, Hot-dip galvanised, DIN EN ISO ..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 5 200 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	US 5 200 FT
Catalog number	6340970
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-309BD9419F
Generated	2026-08-02

Product Overview

U support 3-sided perforated, 50x50x2000, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
U-Profile US 5 200 FT, 3-sided perforated 50x50x2000 Steel, St, Hot-dipped galvanized, DIN EN ISO 1461
US 5 support FT. U support in fixed lengths. Dimensions 50 x 50 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories
--------------	--

Additional Product Information

Breakable no
CO2 Footprint (GWP) Cradle-to-Gate 11,2907 kg CO2e / 1 Piece
Colour zinc
Dimension 50 x 50 x 2,5
Dimension 50x50x2000
Dimension L 2000 mm
EPD article yes
Height 50 mm
Length 2000 mm
Maintain electrical functions yes
Material Steel
Material thickness 2,5 mm
Profile shape U profile

Slot width 45 mm
Static value A 2,74 cm²
Static value Iy 8,32 cm⁴
Static value Iz 12,53 cm⁴
Static value Wy 2,61 cm³
Static value Wz 5,01 cm³
Surface Hot-dip galvanised
Type of perforation 3 sides perforated
Version for Single profile
Width 50 mm
With tothing no
ETIM for 6340970 Fixings and fasteners (EC000386)
Feature Name
Feature Value
Length (EF001438)
2000 mm
Width (EF000008)
50 mm
Height (EF000040)
50 mm
Material thickness (EF000386)
2.5 mm
Profile shape (EF005179)
U-profile
Type of perforation (EF004147)
3 sides perforated
With tothing (EF000571)
No
Area moment of inertia Iy (EF012513)
8.32 cm⁴
Area of inertia Iz (EF012514)
12.53 cm⁴
Moment of resistance Wy (EF012503)
2.61 cm³
Moment of resistance Wz (EF012504)
5.01 cm³
Suitable for circuit integrity (EF007806)
Yes
Material (EF002169)
Steel
Surface protection (EF000139)
Hot dip galvanized
Weight (EF000167)
5.06 kg

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 5 200 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.