

INDUSTRIAL COMPONENT DATA

US 5 60 FT 6340946 OBO BETTERMANN U support 3-sided perforated, 50x50x600, Hot-dip galvanised, DIN EN ISO 14..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 5 60 FT



Manufacturer	OBO BETTERMANN
MPN / Reference	US 5 60 FT
Catalog number	6340946
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-FB102237F3
Generated	2026-07-29

Product Overview

U support 3-sided perforated, 50x50x600, Hot-dip galvanised, DIN EN ISO 1461, Steel, St
US 5 support FT. U support in fixed lengths. Dimensions 50 x 50 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories
--------------	--

Additional Product Information

Breakable no
CO2 Footprint (GWP) Cradle-to-Gate 3,5466 kg CO2e / 1 Piece
Colour zinc
Dimension 50x50x600
Dimension 50 x 50 x 2,5
Dimension L 600 mm
EPD article yes
Height 50 mm
Length 600 mm
Maintain electrical functions yes
Material Steel
Material thickness 2,5 mm
Profile shape U profile
Slot width 45 mm

Static value A 2,74 cm²
Static value I_y 8,32 cm⁴
Static value I_z 12,53 cm⁴
Static value W_y 2,61 cm³
Static value W_z 5,01 cm³
Surface Hot-dip galvanised
Type of perforation 3 sides perforated
Version for Single profile
Width 50 mm
With tothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 5 60 FT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.