

**INDUSTRIAL COMPONENT DATA**

# US 5 70 FT 6340950 OBO BETTERMANN U support 3-sided perforated, 50x50x700, Hot-dip galvanised, DIN EN ISO 14..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 5 70 FT



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | OBO BETTERMANN         |
| MPN / Reference | US 5 70 FT             |
| Catalog number  | 6340950                |
| Category        | Mounting rail/-profile |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-BBB5108354          |
| Generated       | 2026-08-02             |

## Product Overview

U support 3-sided perforated, 50x50x700, Hot-dip galvanised, DIN EN ISO 1461, Steel, St  
US 5 support FT. U support in fixed lengths. Dimensions 50 x 50 mm.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories |
|--------------|------------------------------------------------------------------------------------|

## Additional Product Information

Breakable no  
CO2 Footprint (GWP) Cradle-to-Gate 4,354 kg CO2e / 1 Piece  
Colour zinc  
Dimension 50x50x700  
Dimension 50 x 50 x 2,5  
Dimension L 700 mm  
EPD article yes  
Height 50 mm  
Length 700 mm  
Maintain electrical functions yes  
Material Steel  
Material thickness 2,5 mm  
Profile shape U profile  
Slot width 45 mm

Static value A 2,74 cm<sup>2</sup>  
Static value I<sub>y</sub> 8,32 cm<sup>4</sup>  
Static value I<sub>z</sub> 12,53 cm<sup>4</sup>  
Static value W<sub>y</sub> 2,61 cm<sup>3</sup>  
Static value W<sub>z</sub> 5,01 cm<sup>3</sup>  
Surface Hot-dip galvanised  
Type of perforation 3 sides perforated  
Version for Single profile  
Width 50 mm  
With toothing no

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 5 70 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.