

INDUSTRIAL COMPONENT DATA

US 5 70 A2 6341121 OBO BETTERMANN U support 3-sided perforated, 50x50x700, Stainless steel, grade 304, VA, 1..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 5 70 A2



Manufacturer	OBO BETTERMANN
MPN / Reference	US 5 70 A2
Catalog number	6341121
Category	Mounting rail/-profile
Minimum order	1 Pcs
Document ID	EO-A6E85C854A
Generated	2026-08-02

Product Overview

U support 3-sided perforated, 50x50x700, Stainless steel, grade 304, VA, 1.4301

U-profile US 5 70 A2 perforated on 3 sides 50x50x700 stainless steel Stainless steel 1.4301, A2, 1.4301 Polished, with post-treatment

US 5 support A2. U support in fixed lengths. Dimensions 50 x 50 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories
--------------	--

Additional Product Information

Breakable no

CO2 Footprint (GWP) Cradle-to-Gate 10,2408 kg CO2e / 1 Piece

Colour stainless steel

Dimension 50x50x700

Dimension 50 x 50 x 2,5

Height 50 mm

Length 700 mm

Maintain electrical functions no

Material Stainless steel 1.4301

Material thickness 2,5 mm

Profile shape U profile

Static value A 2,74 cm²

Static value I_y 8,32 cm⁴
Static value I_z 12,53 cm⁴
Static value W_y 2,61 cm³
Static value W_z 5,01 cm³
Surface Bright, treated
Type of perforation 3 sides perforated
Version for Single profile
Width 50 mm
With toothing no

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 5 70 A2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.