

**INDUSTRIAL COMPONENT DATA**

# US 7 170 FT 6340253 OBO BETTERMANN U support 3-sided perforated, 70x50x1700, Hot-dip galvanised, DIN EN ISO ..

Brand: OBO BETTERMANN | Manufacturer Part Number: US 7 170 FT



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | OBO BETTERMANN         |
| MPN / Reference | US 7 170 FT            |
| Catalog number  | 6340253                |
| Category        | Mounting rail/-profile |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-7E838080F9          |
| Generated       | 2026-07-29             |

## Product Overview

U support 3-sided perforated, 70x50x1700, Hot-dip galvanised, DIN EN ISO 1461, Steel, St

U-profile US 7 170 FT, perforated on 3 sides 70x50x1700 Steel, St, Hot-dip galvanized, DIN EN ISO 1461

US 7-Stem FT

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| Catalog path | OBO BETTERMANN > KTS cable support systems - OBO BETTERMANN > mounting accessories |
|--------------|------------------------------------------------------------------------------------|

## Additional Product Information

U-stem in fixed lengths. Dimensions 70 x 50 mm.

ETIM for 6340253 Fixings and fasteners (EC000386)

Feature Name

Feature Value

Length (EF001438)

1700 mm

Width (EF000008)

70 mm

Height (EF000040)

50 mm

Material thickness (EF000386)

4 mm

Profile shape (EF005179)

U-profile

Type of perforation (EF004147)

3 sides perforated

With tothing (EF000571)

No

Area moment of inertia  $I_y$  (EF012513)

13.79 cm<sup>4</sup>

Area of inertia  $I_z$  (EF012514)

36.84 cm<sup>4</sup>

Moment of resistance  $W_y$  (EF012503)

4.11 cm<sup>3</sup>

Moment of resistance  $W_z$  (EF012504)

10.53 cm<sup>3</sup>

Suitable for circuit integrity (EF007806)

Yes

Material (EF002169)

Steel

Surface protection (EF000139)

Hot dip galvanized

Weight (EF000167)

6.86 kg

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send OBO BETTERMANN / US 7 170 FT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.